

Wellwasser HOME Edition V8

Water treatment system for the production of water (wellwasser[®]) in demanding households, nursing and retirement homes and health care facilities.

Enjoy premium water in its purest form.

- DRINKING: Supply of crystal-clear, top quality drinking water, pure or for the dilution of fruit juices.
- WASHING: Washing food with germ-free and clean water (wellwasser[®]).
- COOKING: wellwasser[®] preserves the natural flavor of your dishes.
- BREWING: Tea, coffee or other brewed beverages unfold their full flavor.



wellwasser[®] is the alternative to bottled mineral water.

Our joint contribution to environmental protection

Technical Details



Activated carbon pre-coat filter 0.5µm

With silver ions to prevent bacterial growth on the filter surface. Removes unpleasant odours and tastes, e.g. chlorine or other unwanted substances in water. Dirt and particles larger than 0.5µm (0.0005mm) are retained on the 0.5µm membrane surface. Asbestos fibres, cysts, cryptosporidium and giardia are filtered out. Organic pollutants such as pesticides or hormones are bound to the activated carbon.

Natural and valuable minerals are retained in the water.
Lifespan: 10,000 litres or 1 year

Wellwasser Activator

Selected crystals stabilize and vitalize the water. The result is incomparable neutral tasting wellwasser®.

Housing: stainless steel 1.4404



Sterilization Filter 0.1µm

Bacteria and germs e.g. Legionella, Pseudomonas or E. coli are reliably removed by ultra-filtration. Filters smallest microplastic traces.

Cut-off: 0.1µm

Percentage of retained bacteria: >99.99999% >LOG 7
Life span: 6 months



Even in a small sink base unit with an undersink water heater there is enough space for the Wellwasser Water Treatment System.

It is connected with standard 3/8" armored hoses.

Suitable for connection to a carbonator (cooling unit for the production of wellwasser® sparkling) or a water fitting.

Dimensions: Height: 480 mm, width: 300 mm, depth: 135 mm

Operating pressure: 1 to 5 bar

Max. flow rate.: 1.9lpm

Water temperature: 2 – 38°C

Connections: R 3/8" AG

Dry weight: 5.8 kg